

A new way to ride in style





Contents

1. Name of each part	0
2. Product features · · · · · · · · · · · · · · · · · · ·	. 02
3. How to unfold · · · · · · · · · · · · · · · · · · ·	. 03
4. How to fold · · · · · · · · · · · · · · · · · · ·	04
5. How to use the dashboard · · · · · · · · · 0	5-06
6. How to charge	. 07
7. Safety precautions for lithium-ion battery 0	8-09
8. Safety driving tips	10
9. Daily protection and maintenance· · · · · · · 1	1-13
10. Product specification · · · · · · · · · · · · · · · · · · ·	4-15
11 Guarantee card	17

Name of each part





Product Features

LED acrylic Light

Using bright LED to light through acrylic rode to create a sleek and beautiful beast in the night or day

A masterpiece

Created by our award winner designer. New innovative ways to brighten up our scooter.



Style yet light

We enchance every aspect with innovation yet without compromising the weight less than 20kgs

Comfortable

comfort is as important as the design. we include front and rear high quality suspension to fit the criteia



How to unfold



Step1:Pull out the red lever



Step2:Extend the T handle bar and fasten the red rods



Step3:Adjust the height of T handle bar



Step4:Fasten the nut and buckle (make sure the stem fixed well)



How to fold



Step 1: power off



Step 2: Loose the red rods and fold the T handle bar



Step 3: unscrew the nut and loose the buckle



Step 4: Pull downward the T handle bar



Step 5: Pull out the red lever, and fold the scooter stem at the same time

How to use the dashboard

Basic operation:

Power Switch

Press the power switch for over 3 seconds, then the LCD screen will turn on. The device will turn off automatically if it doesn't move after 180 seconds.

Speed Control

After power on, press mode switch to show speed level (L1-Low seep, L2 -medium speed, L3 high speed)

Press mode switch 3 seconds, lights will turn on.

Power Indication

Number of bars indicates the rest power of lithium battery.

Note: Recharge when there is only one bar, beacuse over discharging may damage the battery.

L CD Screen

After power on, press the power key to change modes:

ODD: accumulate milage TRIP: Current mileage VOL: Current voltage (Volt)





How to use the dashboard



Gear(1,2,3)

How to charge



- 1)As shown in the picture, open the charging ports and connect them to the charger's connector and connect them into a household outlet.
- ${\bf 2) Charging\ status\ indicator, Red: not\ fully\ charged, Green: fully\ charged.}$
- 3)If the charger indicates green light, it is fully charged, so disconnect the charger and remove it.
- 4)When connecting the connector to the charging port, metallic sparks due to the voltage difference may occur, but this is normal.

CAUTION:

- 1. We recommend that you always use a dedicated charger.
- Performance and safety are not guaranteed when using a charger other than the dedicated charger.
- 2. Charger failure may cause a fire while charging.
- Be sure to disconnect the charger terminal when you leave the place for a time.
- 3. If the child uses a charger, please use it under the supervision of a guardian.
- 4. After unplugging the charger, do not touch the plug for about 10 seconds.






Safety precautions for lithium-ion battery

- 1)Only use the charger that was supplied with your product to charger lithium—ion battery. Use of an unauthorized charger could cause serious damage to the battery and can cause fire.
- 1)Charge lithium—ion battery within 0–45°C and discharge within –20–60°C. Charging and discharging the battery not within the appropriate temperature may damage the lithium—ion battery.
- 2)Don not leave lithium-ion battery in any place exposed to direct sunlight or high temperature. Don not store it in wet places. Always store it in dry places.
- 3)Charge lithium-ion battery in dry,open,and well-ventilated place.Do not charge the battery near inflammable goods.
- 4)In the winter, bring the battery from outside to inside, the temperatures changed from low to high and this many cause dew condensation. In this case, don not charge the battery immediately, but charge it after reducing temperature difference.
 5)If the battery protection circuit is damaged, the battery emits an unusual smell,
- or the battery leaks, contact the authorized service center immediately and get technical support.
- 6)Put lithium-ion battery in a safe place out of the reach of children and pets.
- 7)Do not reverse the polarity on a battery and short-circuit. Also exposing the battery to excessive shock can result in an explosion of the battery.
- 8)Do not do stunts or jumps on the product on bumpy surfaces.
- Exposing a battery pack to excessive shock can result in fire on the battery. If there are some crashes while driving, then you should remove it out of the product to check whether the battery is working well.

Safety precautions for lithium-ion battery

- 9)Connecting the charger when the product is waterlogged, the risk of electric shock and fire is very high. Do not charge the battery in this case and the battery should be checked by an expert before charging.
- 10)Do not disassemble or incinerate lithium-ion battery.
- To safely dispose of lithium-ion battery ,put it as industrial waste and be careful not short-circuit occurs in terminals.
- 11)If the battery requires replacement after long-term use, replace it with the new one through the authorized dealer.
- 12)Do not use the battery if the leaks or fives off an odor, and short–circuit inside the battery pack. Lithium–ion is inflammable material. Avoid charging the battery without proper care. Be very alert to the time that you have charged the battery to prevent fire.
- 13)External temperature effects much on the battery. In winter, when the temperature is low, the performance of the battery degrades, driving distance and power are reduced, and when the weather gets warmer, it returns to its original state.
- 14)When the scooter needs to be stored long time without using,keep it with charging around 70–80% from the max charging.
- 15)If a product with a lithium—ion battery detects overheating ,smoke,or ignition, you should stop charging and using it immediately,move the product outdoors as soon as possible, and then evolve using a fire extinguisher. As it is more dangerous, do not spill or immerse the water on the product to evolve.

Safety driving tips



- To prevent a safety accident, wear safety gears such as comfortable hoes, knee protector, helmet and elbow protector. Rider should comply with the Road Traffic Law.
- 2) The scooter is not waterproof product. Never use when it is rainy or snowy and if the road is wet or icy. The damage from the water is not free even though it is in warranty period.
- 3) Changing the settings of dashboard may result in a safety hazard. If you need change the settings, please ask for help from expert or authorized dealer.
- 4) When turning left and right, make sure that there are no obstacles and then turn slowly with keeping a wide turning radius.
- 5) For the night driving, check the position of the light and the state of the taillight when you hold the brake.

Daily protection and maintenance

Clean and storage of electric scooter

If there is stain on the surface of the scooter, just use soft cloth with clean water to scrub, if there is stubborn stain, please apply with toothpaste a. and then clean with wet cloth, if there is scratch on the plastic part, use abrasive paper or other abrasive material to polish.

Note: Do not use alohol, gasoline. kerosene or other corrosive chemical solution to clean, otherwise the appearance or internal structure of the scoter may be damaged. It's fobidden to flush with hydraulic cannon. Make sure the electric scooter is powered off and disconected with power cord and the cover of charging port is closed when cleaning: otherwise electric shock or serious fault may occur due to penetration of water.

When disused, it's suggested to store the electric scooter at dry and cool place in house. Outdoor string for a long time should be avoided. Outdoor (environment with blazing sun, too hot or cold weather will speedup the aging process of overall appearance and tyres, and shorten the service lifetime of the electric scooter and its battery set.

Folding and handling



Make sure the electric scooter is powered off, hold the tube and push aside the thumb shifter, then open the folding lever.





Daily protection and maintenance



Handling

Handing he scooter by holding the tube with one hand or two hands.

Adjusting brake



If the brake is too tight, use a M5 hex wrench to loose the bolts of tension disc on the brake base by rotating anticlockwise, and then withdraw the brake cord (the exposed length decreases) and fasten the bolts of tension disc, If the brake is too loose, unscrew the bolts of tension disc and pull out the brake cord (the exposed length increases) and then fast the bolts of tension disc.

Daily protection and maintenance

Adjusting shaking handles



If the vertical tube shakes during your riding the scooter, please use a M5 hex wrench to fasten the two bolts at the folding mechanism.

Use of inflation inlet



If the tyres are insufficiently inflated, please inflate them in time, so as to avoid damage of the tyres.





Product specfication

	Product Name	Maxspeed X8
	Single HUB Motor	36V 400Watt / 48V 600Watt
	Motor Cover Material	Aluminum Alloy
	Max Power	400Watt / 600Watt
	Max Speed	35km/h / 45km/h
	Max Mileage	36V 10.4AH (25-30KM) , 48V 13AH (35 -40KM)
Ī	Gradeability(Max Uphill Climb Ability)	15° Max Road Inclination
	Battery Type	Lithium-ion Battery (china or LG)
	Battery Capacity	36V 10.4AH 148V 13AH
	Lights	LED Front Light & Tail light / Brakelight / Acrylic light
	Braking	Rear Drum brake + E-ABS Brake System
	Tires	8 Inch On-road Tires
	Suspension	Front and rear Spring Suspension
	Dashboard	blue Smart Display
	Display Functions	Battery, Trip, ODO, Time, Speed, Mode, Cruise Control and Magnetic Brake
	Folding	5 Sec- folding
	Body Frame	Ultra strong aluminum alloy
	Covers Material	Polypropylene
	Max Rider Weight	120kg
	Product Size	104*21.5*114 CM (Open size)
	Product Weight	14kg / 17.5kg
	Box size	103*29.5*40 CM
	Colour	Black, White and Blue

Product specfication

Product Name	Maxspeed X9
Single HUB Motor	36V 400Watt / 48V 600Watt
Motor Cover Material	Aluminum Alloy
Max Power	36V 400Watt / 600Watt
Max Speed	35km/h / 45km/h
Max Mileage	36V 10.4AH (25-30KM) , 48V 13AH (40KM) 15.6AH (50KM)
Gradeability(Max Uphill Climb Ability)	15° Max Road Inclination
Battery Type	Lithium-ion Battery (china or LG)
Battery Capacity	36Volt 10AH / 48V 13AH / 48Volt 15.6AH
Lights	LED Front Light & Tail light / Brakelight / Acrylic light
Braking	Rear Drum brake + E-ABS Brake System
Tires	8.5 Inch On-road Air Tires
Suspension	Front and rear Spring Suspension
Dashboard	blue Smart Display
Display Functions	Battery, Trip, ODO, Time, Speed, Mode, Cruise Control and Magnetic Brake
Folding	5 Sec- folding
Body Frame	Ultra strong aluminum alloy
Covers Material	Polypropylene
Max Rider Weight	120kg
Product Size	110*21.5*114 CM
Product Weight	14.5kg / 18kg / 19.5kg
Box size	109*29.5*40.5CM
Colour	Black, White and Blue

Guarantee card

s	tart date of warranty extension	(DDMMYY)			
S	tart date of warranty extension	(DDMMYY)			
S	tart date of warranty extension	(DDMMYY)			
Usei	User information:				
Name :					
Con	Contact number :				
Ema	Email:				
Addı	Address:				
Proc	Product information				
Mod	el:				
Rep	air station:				
Date	e of return:				
Faut	t disruption:				
Faul	t cause:				

Signature of the repairer : _____